

Customer Drawing

RECOMMENDED PCB LAYOUT (± 0.05)

NOTES:

1. VOLTAGE RATING: 600V DC;
2. CURRENT RATING: 95A;
3. CONTACT RESISTANCE $\leq 0.5m\Omega$;
4. INSULATING RESISTANCE $\geq 3000M\Omega$;
5. WITHSTAND VOLTAGE: 2500V AC;
6. DURABILITY: 200 CYCLES;
7. WORK TEMPERATURE: $-40^{\circ}C \sim 125^{\circ}C$;
8. CONTACT PARTS PLATING: Ag PLATING;
9. PRODUCT ROHS COMPLIANCE;

5		Male pin(long)	1	red copper	NO.3
4		Male pin(standard)	3	red copper	NO.1、2、4
3		Fixed foot	2		
2		Male clamp	1		
1		Male housing	1		
Serial number	Part Number	Description	Quantity	Materials	Notes
UNLESS OTHERWISE SPECIFIED TOLERANCES X +/- 0.50 JXX +/- 0.30 JXXX +/- 0.10 FRACTIONS +/- ANGLES +/- 5° FOR MATERIALS AND FINISHES SEE NOTES REMOVE SHARP EDGES DIMENSIONS U.S. INCHES —METRIC— —MM— APPROVAL DRAWN CHECKED CHECKED DATE DRAWING FILE : ANGLE OF PROJECTION 					

SHENZHEN MEDLON HARDWARE PRODUCT CO., LTD

TITLE:
PLUG POWER CONNECTOR
JDC 4 CORES (95A)

SIZE DRAWING NO.
A4 JDC-4T-005

REV.
A


SCALE NONE SHEET 1 OF 1

NOTES:

1. VOLTAGE RATING: 600V DC;
2. CURRENT RATING: 95A;
3. CONTACT RESISTANCE $\leq 0.5m\Omega$;
4. INSULATING RESISTANCE $\geq 3000M\Omega$;
5. WITHSTAND VOLTAGE: 2500V AC;
6. DURABILITY: 200 CYCLES;
7. WORK TEMPERATURE: $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$;
8. CONTACT PARTS PLATING: Ag PLATING;
9. PRODUCT RoHS COMPLIANCE;

5		Male pin(long)	1	red copper	NO.3
4		Male pin(standard)	3	red copper	NO.1、2、4
3		Fixed foot	2		
2		Male clamp	1		
1		Male housing	1		
Serial number	Part Number	Description	Q uantity	M aterials	Notes

UNLESS OTHERWISE SPECIFIED TOLERANCES		APPROVAL		DATE	
U.S.	METRIC	DRAWN			
.X +/-	0.50	CHECKED			
.XX +/-	0.30	CHECKED			
.XXX +/-	0.10				
FRACTIONS +/-					
ANGLES +/-	°				

FOR MATERIALS AND FINISHES SEE NOTES		DRAWING FILE :		SHENZHEN MEDLON HARDWARE PRODUCT CO., LTD	
REMOVE SHARP EDGES		ANGLE OF PROJECTION		TITLE:	
DIMENSIONS				PLUG POWER CONNECTOR	
U.S. INCHES				JDC 4 CORES (95A)	
—METRIC— —MM—		SIZE DRAWING NO.		REV.	
		A4 JDC-4T-005		A	
		SCALE NONE		SHEET 1 OF 1	